

ROLL LABEL - SPECIALI

Issue date : 10/03/2009
Date last modification : 13/01/2012**06077 LASER FIT PET 50 GLOSS WHITE TC AP901 WK100****Face Material**

Gloss white thermostabilized top coated polyester.

Type	Thermostabilized polyester		
Colour and Finish	Gloss white		
Weight	70 g/m ² ±10%	ISO-536	
Thickness	50 μ ±10%	ISO 534-80	

Adhesive

Acrylic permanent adhesive featuring high clarity and cohesion with strong adhesion to apolar substrates (like PE and PP).

Reference	AP901		
Type	Acrylic permanent		
Min. Appl. Temp.	-5°C		
Service Temp.	-40°C/+120°C		
Shear	High		
Tack	8 N/25mm	FINAT FTM9	
Final Adhesion	7 N/25mm	FINAT FTM2	

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

Liner

Type	One side siliconised clay coated Kraft		
Colour and Finish	White		
Weight	100 g/m ² ±10%	ISO 536	
Thickness	108 μ ±10%	ISO 534	
Transparency	n.a. %	DIN 53 147-64	

Applications

Office informative labels (like archives or files) and labelling in the logistic field (like identification or signalization labelling). Available in rolls and sheets.

Printing Methods

Printable by photocopy machines and colour and monochrome laser printing.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life36 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



Ritrama S.p.A.

Via Senatore Simonetta, 24
20867 Caponago (MB) ITALY
e-mail: info@ritrama.com
www.ritrama.com