

Galerie™ Brite is a coated publication paper available in reels for heatset web offset printing

Technical specifications

Parameter	Standard	Unit						
Basis weight	ISO 536	g/m²	54	57	60	65	70	80
Brightness (illuminant D65/10°)	ISO 2470-2	%	83	85	86	86	87	87
Gloss 75°	ISO 8254-1	%	46	48	51	55	56	57
Opacity	ISO 2471	%	92	92	93	94	95	96
Bulk	ISO 534	cm³/g	0,92	0,89	0,89	0,88	0,88	0,88


Wrapping

ISO 50001

Kraft paper laminated with polyethylene. The wrapping is recyclable.

Mill Certification

	EMAS	The environmental performance is monitored and continuously improved accord-
EIV	EMAS	ing to the requirements of Eco-Management and Audit Scheme (EMAS).



The environmental aspects of the mill are managed according to the requirements of ISO 14001.

The energy consumed and the emissions generated by the mill are managed according to ISO 50001.

OHSAS The health and safety of the mill employees are managed according to the requirements of OHSAS 18001.

All fibers from sustainable and controlled sources. PEFC™ may have limited availability, please check with your local sales office.

All fibers from sustainable and controlled sources. FSC® limited availability , please check with your local sales office.

Product Certification



All fibers from sustainable and controlled sources. PEFC™ may have limited availability, please check with your local sales office.

All fibers from sustainable and controlled sources. FSC® may have limited availability, please check with your local sales office.

The key environmental parameters of the product are presented at the Paper Profile.

Meets the purity requirements (heavy metal content) of EN 71-3 'Toy Safety', part 3 'Migration of certain elements' and part 9 'Organic chemical compounds'.

The product is awarded an EU Ecolabel and inspected for Nordic Ecolabelled printing. Packaging of product complies with packaging and waste directive 94/62/EC (article 11). Galerie Brite is fully recyclable.