



Galerie™ fine silk

Coated publication paper available in reels for heatset web offset printing

Technical specifications

PARAMETER	STANDARD	UNIT	STANDARD QUALITY VALUES								
BASIS WEIGHT	ISO 536	g/m²	65	70	75	80	90	100	115	130	
BRIGHTNESS <small>(illuminant D65/10°)</small>	ISO 2470-2	%	92	93	93	94	95	97	98	99	
GLOSS 75°	ISO 8254-1	%	35	35	35	35	35	45	45	45	
OPACITY	ISO 2471	%	93	94	94,5	95	95	95	96	97	
BULK	ISO 534	cm ³ /g	0,94	0,94	0,93	0,92	0,92	0,86	0,86	0,86	

Print recommendations

Recommendation for printing conditions	Fogra 39 characterisation data.
Recommendation for max. TAC %	320%
Screen ruling	60-80/cm Suitable with all existing half tone technologies.
Processing	Allow paper to acclimatise to press room conditions/temperature before removing outer packaging. Wrappers should be removed only when ready to print.

For more detailed recommendations please refer to the pre-press datasheet or contact your local sales office.

Reel specifications

Reel width	400 – 2600 mm
Diameters	1000, 1250 mm
Max weight	4000 kg
Core	76 mm

Wrapping

Kraft paper laminated with polyethylene. The wrapping is recyclable.

Product and mill certifications

MILL CERTIFICATION						PRODUCT CERTIFICATION					
EMAS	ISO 14001	ISO 9001	OHSAS 18001	PEFC C.o.C	FSC™ C.o.C	ECF	PEFC credit material	FSC™ Mix	Food contact	Toy safety	Paper profile
✓	✓	✓	✓	✓		✓	✓				✓

- FSC™ & PEFC may have limited availability, please check with your local sales office.
- Packaging of product complies with packaging and waste directive 94/62/EC (article 11).
- Galerie fine silk is fully recyclable.
- To learn more about all these certifications and to receive copies please contact your local sales office.

Target production values.

Regional variations in specifications may apply; please contact your local Sales office for more information.

Updated: 11/07/2014 Region: __

